



Kelylands EV Charger American Standard SAE J1772

NINGBO KELYLANDS CAR ACCESSORY CO., LTD

Add: No.229 YongAn West Road, Kandun Town,
Cixi, Ningbo, Zhejiang, China 315303

Tel: (086) 574 8731 2232

Fax: (086) 574 6303 7038

Mob: (086) 170 5109 5790

Web: www.kelylands.cn

Email: sales@kelylands.cn

AC American standard TYPE 1 [LEVEL 1]
16A charging gun



● Product physical picture

Product name: American standard TYPE 1
16A charging gun indicator [LEVEL 1]

charging plug: SAE J1772 Main plug: LEVEL 1

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 2.6KG

input: 110V

output: 110V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*2.5MM²+0.75MM²

Housing material: PC9330

Single packing specification: 34CM*24.5CM*16CM

AC American standard TYPE 1 [LEVEL 2]
16A charging gun



● Product physical picture

Product name: American standard TYPE 1
16A charging gun indicator [LEVEL 2]

charging plug: SAE J1772 Main plug: LEVEL 2

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 2.6KG

input: 110V

output: 110V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*2.5MM²+0.75MM²

Housing material: PC9330

Single packing specification: 34CM*24.5CM*16CM

AC American Standard 32A Indicator Charging Gun



● Product physical picture

Product name: American standard TYPE 1
32A charging gun indicator

charging plug: SAE J1772

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 4.1KG

input: 240V

output: 240V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*6MM²+0.75MM²

Housing material: PC9330

Single packing specification: 41CM*41CM*9.5CM

AC American Standard Type 1 [LEVEL 1]
16A screen display



● Product physical picture

Product name: American Standard TYPE 1
16A charging gun screen display [LEVEL 1]

charging plug: SAE J1772 Main plug: LEVEL 1

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 2.6KG

input: 110V

output: 110V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*2.5MM²+0.75MM²

Housing material: PC9330

Single packing specification: 34CM*24.5CM*16CM

AC American Standard Type 1 [LEVEL 2]
16A screen display



● Product physical picture

Product name: American Standard TYPE 1
16A charging gun screen display [LEVEL 2]

charging plug: SAE J1772 Main plug: LEVEL 2

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 2.6KG

input: 110V

output: 110V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*2.5MM²+0.75MM²

Housing material: PC9330

Single packing specification: 34CM*24.5CM*16CM

AC American standard 32A screen display charging gun



● Product physical picture

Product name: American Standard Type 1
Indicator 32A Charging Gun

charging plug: SAE J1772

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 4.1KG

input: 240V

output: 240V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*6MM²+0.75MM²

Housing material: PC9330

Single packing specification: 41CM*41CM*9.5CM

AC American Standard makes an appointment for fourth gear. [LEVEL 1]



● Product physical picture

American standard TYPE1 16A reserved fourth gear [LEVEL 1]

charging plug: SAE J1772 Main plug:LEVEL 1

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 2.6KG

input: 110V

output: 110V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*2.5MM²+0.75MM²

Housing material: PC9330

Single packing specification: 34CM*24.5CM*16CM

AC American Standard makes an appointment for fourth gear. [LEVEL 2]



● Product physical picture

American standard TYPE1 16A reserved fourth gear [LEVEL 2]

charging plug: SAE J1772 Main plug:LEVEL 2

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 2.6KG

input: 110V

output: 110V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*2.5MM²+0.75MM²

Housing material: PC9330

Single packing specification: 34CM*24.5CM*16CM

AC American Standard 32A appointment
five gear charging gun



● Product physical picture

Product name: American Standard TYPE 1
5-gear 32A charging gun

charging plug: SAE J1772

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 4.1KG

input: 240V

output: 240V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*6MM²+0.75MM²

Housing material: PC9330

Single packing specification: 41CM*41CM*9.5CM

AC American Standard TYPE 1 [Plug and Charge] Charge Point



● Product physical picture

Product name: AC American Standard TYPE 1
[Plug and Charge] Charge Point

charging plug: SAE J1772

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 5KG

input: 240V

output: 240V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*6MM²+0.75MM²

Housing material: PC9330

Single packing specification: 41CM*41CM*13CM

AC American Standard [Card swiping five gear switch] Charge pile



● Product physical picture

Product name: AC American Standard
[Card swiping five gear switch] Charge Point

charging plug: SAE J1772

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 5KG

input: 240V

output: 240V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*6MM²+0.75MM²

Housing material: PC9330

Single packing specification: 41CM*41CM*13CM

AC American Standard [Card swiping start] Charge Point



● Product physical picture

Product name: AC American Standard
[Card swiping start] Charge Point

charging plug: SAE J1772

Power cord length: 5 meters [Minimum 200 glass panels]

Product weight: 5KG

input: 240V

output: 240V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*6MM²+0.75MM²

Housing material: PC9330

Single packing specification: 41CM*41CM*13CM

AC American Standard [Card swiping start]
screen display charging pile



● Product physical picture

Product name: AC American Standard
[Card swiping start] screen display charging pile

charging plug: SAE J1772

Power cord length: 5 meters [Minimum 200 glass panels]

Product weight: 5KG

input: 240V

output: 240V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*6MM²+0.75MM²

Housing material: PC9330

Single packing specification: 41CM*41CM*13CM

AC American standard TYPE 1 [Europe to America] extension cable



● Product physical picture

Product name: AC American standard TYPE 1
[Europe to America] charging gun extension line

charging plug: SAE J1772

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 5KG

input: 240V

output: 240V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

working temperature: -30°C -120°C

Operating humidity: 5%-95%

Cable: 3*6MM²+0.75MM²

Housing material: PC9330

Single packing specification: 41CM*41CM*9.5CM