



Kelylands EV Charger

European Standard

IEC62196-2

NINGBO KELYLANDS CAR ACCESSORY CO., LTD

Add: No.229 YongAn West Road, Kandun Town,
Cixi, Ningbo, Zhejiang, China 315303

Tel: (086) 574 8731 2232

Fax: (086) 574 6303 7038

Mob: (086) 170 5109 5790

Web: www.kelylands.cn

Email: [sales @ kelylands.cn](mailto:sales@kelylands.cn)

AC European Standard Type 2 Indicator 16A Charging Gun



● Product physical picture

Product name: European standard
charging gun 16A3.5KW [type of indicator light]

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 2.6KG

Input: 220V

Output: 220V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 2.5MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 34CM * 24.5CM * 16CM

AC European Standard Type 2 Indicator 16A Charging Gun



Product physical picture

Product name: European standard
charging gun 32A7KW [indicator type]

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 4.2KG

Input: 220V

Output: 220V AC 32A

Rated power: 7KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 9.5CM

AC European standard TYPE 2- screen display 16A charging gun



● Product physical picture

Product name: European standard
charging gun 16A3.5KW [screen display model]

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 2.6KG

Input: 220V

Output: 220V AC 16A

Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 2.5MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 34CM * 24.5CM * 16CM

AC European standard TYPE 2- screen display 32A charging gun



Product physical picture

Product name: European standard
charging gun 32A7KW [screen display mode]

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 4.2KG

Input: 220V

Output: 220V AC 32A Rated power: 7KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 9.5CM

AC European Standard TYPE 2
appointment fourth gear 16A charging gun



Product physical picture

Product name: European standard
charging gun 8A/10A/13A/16A [reserve four versions]

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 2.6KG

Input: 220V

Output: 220V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 2.5MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 34CM * 24.5CM * 16CM

AC European Standard TYPE 2
Appointment of 5-gear 32A charging gun



Product physical picture

Product name: European standard
charging gun 8A/10A/13A/16A/32A [five files reserved]

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 4.2KG

Input: 220V

Output: 220V AC 32A

Rated power: 7KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 9.5CM

AC European Standard TYPE 2 Plug and Play Charging Post



Product physical picture

Product name: European standard
charging pile 32A [plug and play version] charging pile

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 5KG

Input: 220V

Output: 220V AC 32A

Rated power: 7KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 13CM

AC European Standard TYPE 2
swiping card to start charging pile



Product physical picture

Product name: European standard
charging pile 32A [card swiping start five gear switch]

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 5KG

Input: 220V

Output: 220V AC 32A

Rated power: 7KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 13CM

AC European Standard TYPE 2
swiping card to start charging pile



Product physical picture

Product name: European standard
charging pile 32A [card swiping start glass panel]

Charging plug: IEC62196-2 type 2

Power cord length: 5m [200 glass panels are required]

Product weight: 5.5KG

Input: 220V

Output: 220V AC 32A

Rated power: 7KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 13CM

AC European Standard TYPE 2 swiping card
to start charging pile with screen display



Product physical picture

Product name: European standard charging
pile 32A [card swiping start with screen display glass panel]

Charging plug: LEC62196-2 type 2

Power cord length: 5m [200 glass panels are required]

Product weight: 5.5KG

Input: 220V

Output: 220V AC 32A

Rated power: 7KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 13CM

AC European Standard TYPE 2 Charge Point 380V11KW



Product physical picture

AC European Standard TYPE 2 Charge Point 380V11KW

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized if more than 5 meters]

Product weight: 10KG

Input: 380V

Output: 380V AC 16A Rated power: 11KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 5 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 13CM

AC European Standard TYPE 2 Charge Point 380V22KW



Product physical picture

Product name: AC European Standard TYPE 2
Charging Pile 22KW380V

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 10KG

Input: 380V

Output: 380V AC 32A

Rated power: 22KW

Protection grade: gun head IP67/control box IP54

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 5 * 6MM²+ 0.75MM²

Housing material: PC9330

Single packing specification: 41CM * 41CM * 13CM

AC European Standard TYPE 2 16A
Single phase Pile Connection Line



Product physical picture

Product name: AC European Standard 16A
Single phase Pile Connection Line

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 3KG

Input: 220V

Output: 220V AC 16A Rated power: 3.5KW

Protection grade: gun head IP67

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 2.5MM²+ 0.75MM²

Single packing specification: 34CM * 24.5CM * 16CM

AC European Standard TYPE 2 32A
Single phase Pile Connection Line



● Product physical picture

Product name: AC European Standard 32A
Single phase Pile Connection Line

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 5KG

Input: 220V

Output: 220V AC 32A Rated power: 7KW

Protection grade: gun head IP67

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Single packing specification: 41CM * 41CM * 9.5CM

AC European Standard TYPE 2 16A
pile line three-phase



Product physical picture

Product name: AC European Standard 16A
three-phase pile connecting wire three-phase

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 6KG

Input: 380V

Output: 380V AC 16A Rated power: 11KW

Protection grade: gun head IP67

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 5 * 2.5MM²+ 0.75MM²

Single packing specification: 41CM * 41CM * 9.5CM

AC European Standard TYPE 2 32A pile
line three-phase



● Product physical picture

Product name: AC European standard 32A
pile connecting wire three-phase

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 6KG

Input: 380V

Output: 380V AC 32A Rated power: 22KW

Protection grade: gun head IP67

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 5 * 6MM²+ 0.75MM²

Single packing specification: 41CM * 41CM * 9.5CM

AC European standard TYPE 2 32A extension line



● Product physical picture

Product name: AC European standard 32A
extension line [male and female]

Charging plug: IEC62196-2 type 2

Power cord length: 5 meters [20 pieces can be customized
if more than 5 meters]

Product weight: 5KG

Input: 220V

Output: 220V AC 32A

Rated power: 7KW

Protection grade: gun head IP67

Operating temperature: - 30 °C - 120 °C

Operating humidity: 5% - 95%

Cable: 3 * 6MM²+ 0.75MM²

Single packing specification: 41CM * 41CM * 9.5CM